

L.11.0 ADDENDUM A – TRAILER DECONTAMINATION AND AIR MONITORING

The procedures outlined in this section are to be implemented to ensure the Site trailer is properly staged, and remains uncontaminated throughout the duration of Site activities.

Trailer Staging

- Place Visqueen liner at designated location for trailer(s).
- Cover liner with protective gravel layer.
- Situate trailer on protective gravel layer.
- Strap the trailer down, to prevent it from tipping over during high wind events.
- Ensure the trailer is grounded.
- Do not provide skirting around base of trailer to ensure ventilation under trailer. A temporary fence will be used to separate the trailer from the contaminant reduction and exclusion zones.

Cleaning Exterior and Interior of Site Trailer

- Utilize pre-moistened cleaning cloths (such as Swiffer brand products) to perform complete wipe down of the trailer. The towelettes include a mild solvent and surfactant to promote cleaning and dust recovery. Wipe the towelettes only in one direction. Replace towelettes when they are visibly soiled.
- Start at roof of one end of the trailer and work progressively towards the other end. Clean the trailer roof first, followed by walls, windows, doors and wheels.
- Place soiled towelettes in heavy duty, 6-mil, plastic bags. Seal bags when not being filled, and once full.
- Utilizing a vacuum equipped with a HEPA filter, vacuum clean all corners, crevices and inside of ventilation system. Place vacuum bags and filters into plastic bags and seal pending disposal.

Routine Trailer Operation

- Keep windows closed. For ventilation, operate the HVAC unit.
- Only use air filters for the HVAC unit that are designed for fine dust and are secured in place.
- Include a heavy duty pre-filter for make up air housing.

- Inspect filters on a weekly basis. Post inspection log near HVAC unit.
- For routine cleaning, vacuum floor of trailer utilizing HEPA filter-equipped vacuum cleaner with nylon bristle brush. Vacuum and wet-mop floor only. Broom or compressed air will not be utilized as these can raise dust.
- Clean interior of trailer at least once a month following the protocol described above.
- Once per month, during periods of intrusive activity (more frequently if visible dust buildup occurs) and prior to occupation following periods of inactivity of longer than two months, collect 8-hour indoor air or wipe sample(s) for asbestos and submit to laboratory for analysis. Samples shall be collected prior to cleaning the trailer.